

PE STATION FOR HAZARDOUS SUBSTANCES



PE STATION FOR DRUMS

For the storage of water-endangering and aggressive media indoors and outdoors

- ◆ Rotationally-molded PE-construction yellow, with black PE-sump tray
- Circumferential stabilizing ribs
- ◆ Ground clearance for internal transport
- ◆ PE perforated plate
- Weather protection with black PE louvre-door, lockable with padlock on customer side
- Document tray in the side wall as standard
- ◆ Sump trays with general technical approval DIBt Berlin
- ◆ Delivered as a kit for easy self-assembly on site



PE-ST-2, Article no. P70-2052-A, with optional shelf set



Safety stoerage depots for 200 liter drums can be found on page 146!



Integrated document storage



PE-ST-4, Article no. P70-2053-A





PE-ST-2, Article no. P70-2052-A



PE-ST-45, Article no. P70-2054-A

Model	PE-ST-2	PE-ST-4	PE-ST-45
External dimensions W x D x H (mm)	1500 x 1100 x 2110	1560 x 1790 x 2110	1560 x 1790 x 2110
Internal dimensions W x D x H (mm)	1220 x 750 x 1330	1220 x 1380 x 1510	1220 x 1380 x 1330
Sump capacity (I)	236	242	450
Capacity, 200 liter drums	2 directly on PE perforated plate	4 directly on PE perforated plate	4 directly on PE perforated plate
	or euro-pallet	or chemical pallet	or chemical pallet
Max. load (kg)	500	1000	1000
Article no., with PE perforated plate	P70-2052-A	P70-2053-A	P70-2054-A

Accessory Article no.

Shelf set for storing small containers or canisters with

2 height-adjustable grid shelves, W x D x H (mm) = $1060 \times 635 \times 1150$, max. load per shelf 200 kg

P70-2056-A



PE STATION FOR HAZARDOUS SUBSTANCES




PE STATION FOR KTC/IBC

For the storage of water-endangering and aggressive media indoors and outdoors

- ♦ Rotationally-molded PE-construction yellow, with black PE-sump tray
- Circumferential stabilizing ribs
- Ground clearance for internal transport
- ◆ PE perforated plate
- ◆ Double wing door lockable
- ◆ Sump trays with general technical approval DIBt Berlin
- ◆ Delivered as a kit for easy self-assembly on site







PE-ST-KT, Article no. P70-2055-A, with double wing door lockable





Model	PE-ST-KT
External dimensions W x D x H (mm)	1770 x 1750 x 2260
Internal dimensions W x D x H (mm)	1450 x 1480 x 1320
Sump capacity (I)	1000
Capacity, KTC / IBC	1
Capacity, 200 liter drum vertical	4
Capacity, 200 liter drum horizontal*	2
Max. load (kg)	2000
Article no., with PE perforated plate	P70-2055-A

^{*} possible only in combination with a drum pallet, Article no. R67-1107-A

