



Explanations see practical informations on page 6 and 84!

OUTDOOR STORAGE FOR KTCs / IBCs

Water protection compartment containers are particularly suitable for storing IBCs / KTCs. They have been proven in use under especially rough industrial conditions, such as intermediate storage facility for hazardous waste, in the electroplating industry. The series F-E water protection compartment containers are for use from one side only. Versions for use from both sides are available on request.

Our standard: natural ventilation and lifting attachments for cranes!

Approval-No.: Z-38.5-122



STATIC APPROVED



WSC-F-E.1-27, with hinged doors and natural ventilation, Article no. C22-5236-C



WSC-F-E.2-54, with sliding doors and natural ventilation, Article no. C22-5240-C



KTC storage unit please see on page 148!



Model	WSC-F-E.1-27	WSC-F-E.2-27	WSC-F-E.1-54	WSC-F-E.2-54
Number of levels	1	2	1	2
External dimensions W x D x H* (mm)	2820 x 1450 x 2190	2820 x 1450 x 3575	5580 x 1530 x 2245	5580 x 1530 x 3575
Internal compartment dimensions W x D x H** (mm)	2700 x 1300 x 1730	2700 x 1300 x 1450	2700 x 1300 x 1720	2700 x 1300 x 1450
Sump capacity (l)	1000	1000	2 x 1000	2 x 1000
Capacity, KTCs / IBCs	2	4	4	8
Article no., with hinged doors and natural ventilation	C22-5236-C	C22-5241-C	-	-
Article no., with sliding doors and natural ventilation	-	-	C22-5226-C	C22-5240-C

* External dimensions plus base plates and rain discharge plate

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, lighting etc.)



WATER PROTECTION COMPARTMENT CONTAINERS



OUTDOOR STORAGE FOR KTCs / IBCs

Our standard: natural ventilation and lifting attachments for cranes!

Approval-No.: Z-38.5-122



WSC-F-E.2-110, with sliding doors and natural ventilation, Article no. C22-5251-C


WSC-F-E.1-70, with sliding doors and natural ventilation in special color, Article no. C22-5224-C



WSC-F-E.2-70, with sliding doors and natural ventilation, Article no. C22-5234-C



WSC-F-E.2-35, with hinged doors and natural ventilation, Article no. C22-5218-C



Model	WSC-F-E.1-35	WSC-F-E.2-35	WSC-F-E.1-70	WSC-F-E.2-70	WSC-F-E.2-110
Number of levels	1	2	1	2	2
External dimensions W x D x H* (mm)	3500 x 1450 x 2245	3500 x 1450 x 3660	6940 x 1530 x 2245	7060 x 1530 x 3660	10380 x 1540 x 3660
Internal compartment dimensions W x D x H** (mm)	3380 x 1300 x 1795	3380 x 1300 x 1500	3380 x 1300 x 1730	3380 x 1300 x 1500	3380 x 1300 x 1500
Sump capacity (l)	1000	1000	2 x 1000	2 x 1000	3 x 1000
Capacity, KTCs / IBCs	3	6	6	12	18
Article no., with hinged doors and natural ventilation	C22-5208-C	C22-5218-C	-	-	-
Article no., with sliding doors and natural ventilation	-	-	C22-5224-C	C22-5234-C	C22-5251-C

* External dimensions plus base plates and rain discharge plate

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, lighting etc.)